

Product Series :	GTV	Brand :	GOTREND
File Version :	GTV-SERIES-V2R2	Editor :	Jerry Chen
Established Date :	2011.09.21	Description :	SMD Power Inductor
Latest Edit Date :	2023.11.10	Product Type :	☒ Standard ☐ Customize



REMINDERS

- ◆ Product information in this catalog is subject to change without notice, and is for reference only. Therefore, please contact GOTREND Technology to check for the latest information before practical application or usage of the products.
- ◆ This catalog contains only typical specifications, please contact GOTREND Technology for further details if you can not find special components or information you need in this catalogue. Please also approve our product specifications or transact the approval sheet for product specifications before ordering.
- ◆ This catalogue only applies to products purchased through GOTREND Technology or its official agencies. This catalogue does not apply to products that are purchased through other third parties.
- ◆ Please read Attention and CAUTION note (for storage, operating, rating, soldering, mounting and handling) in this catalog to ensure product proper usage.
- ◆ GOTREND Technology is not responsible for issues that occur related to the intellectual property rights or other rights of our company or a third party when you use a product listed in this catalog. GOTREND Technology do not grant license of these rights.
- ◆ Information and data provided in the brochure can and do vary in different applications, and actual performance may vary over time.
- ◆ "Delivery Specification" illustrating precautions for the specifications and safety of each product listed in this catalog is available and we strongly recommend to provide these delivery specifications with customers that use these products.
- ◆ For exporting of product in this catalog, please take note it may be a restricted item according to the "Foreign Exchange and Foreign Trade Control Law". In such cases, it is necessary to acquire export permission in accordance to this law.
- ◆ Any reproduction or extraction of the contents in this catalog is prohibited without prior permission from GOTREND Technology.
- ◆ Products listed in this catalog are intended for general electronic device usage under normal operation and use condition including telecommunication equipment, home appliances, sports equipment AV equipment, industrial machine, office equipment etc. Please take note that our products are not designed, intended or authorized for use in below mentioned applications unless explicitly agreed in writing between the parties to avoid product failure that could result in situation where personal injury or death could occur.

- (1) Aerospace/Aviation equipment
- (2) Atomic energy-related equipment
- (3) Disaster prevention/crime prevention equipment
- (4) Electric heating apparatus, burning equipment
- (5) Medical equipment
- (6) Military equipment
- (7) Power-generation control equipment
- (8) Public information-processing equipment
- (9) Safety equipment
- (10) Seabed equipment
- (11) Transportation control equipment
- (12) Transportation equipment (cars, electric trains, ships, etc.)
- (13) Other applications that are not considered general-purpose applications

- ◆ Our manufacturing sites fully compliance with requirement regarding the quality management system in the automotive industry under the IATF 16949 standard. GOTREND Technology respect individual agreements with reference to customer requirements and customer specific requirements (CSR). We will like to emphasize that only requirements mutually agreed upon will in implemented in our Quality Management System taking into consideration that IATF 16949 may appear to support the acceptance of unilateral requirements. We will only legally bind to this individually agreed upon agreement under the IATF 16949 standard.
- ◆ The product itself is a powder metallurgy product, so the structure is relatively fragile, and it should not be used for products that are easy to fall. In addition, when this product is assembled, it should avoid collision with the tool or mechanism shell.



- ◆ It is not recommended to use hot air gun for disassembling of this product. When using of hot air gun to repair other parts, please also take note that long time or high temperature exposure of this product will also damage the inductance device. If you need to use the hot air gun to disassemble the product, it is recommended to adjust the hot air gun temperature to 380 deg.C±5 deg.C. The blower head of the hot air gun should be perpendicular and at least 1cm away from the product. After heating the product to the tin material melting point, use tweezers to remove the product from the PCB.





Product Series :	GTV	Brand :	GOTREND
File Version :	GTV-SERIES-V2R2	Editor :	Jerry Chen
Established Date :	2011.09.21	Description :	SMD Power Inductor
Latest Edit Date :	2023.11.10	Product Type :	☒ Standard ☐ Customize

Features & Application :

- * Portable electronics
- * Servers and workstations
- * Data networking and storage systems
- * Notebook and desktop computers
- * Graphics cards and battery power systems
- * Multi-phase regulators
- * Voltage Regulator Module (VRM)
- * DCR sensing

Changed all Marking uses inductance value



(Picture for reference only)

Basic Information :

Made in	China
Pin Foot	SMD
Shielding	Yes
J-STD-020	MSL Level 1
RoHS	Compliant
REACH	Compliant
Halogen	Free

Operating & Storage Condition :

* Operating Temp	-40 ~ +125 °C (Including self - temperature rise)
* Storage Temp	1. -10 ~ +45 °C 50 ~ 60% RH (Product with taping) 2. -40 ~ +125 °C (On board)
* Storage Life Time	6 Month (Less than 40 °C and 60% RH)

Part No. Example :

PN	:	GTV 986480	P	[]	-	R10	K
ID	:	1	2	3	4	5	6
1	:	GOTREND Series : GTV					
2	:	Dimension Code : 9.8 x 6.4 x 8.0 mm					
3	:	P = Pb free < 1000 ppm					
4	:	[R1 ~ R□] : Different DCR Spec. ; [V] : Vertical type					
5	:	[L] Value Ex : R10 = 0.10 uH ; 72N = 0.72 uH					
6	:	Tolerance : K = +/-10%					

Attention & Caution :


- * Keep out of Splashing water or salt water
- * Avoid Toxic Gas (Hydrogen sulfide, Sulfurous acid, Chlorine, Ammonia)
- * Avoid Vibrations or shocks which exceed the specified condition
- * Avoid Dew condense
- * Avoid Layout near the edge of PCB
- * Avoid Over flexure after SMT mounting & PCBA
- * Pin foot or SMD pad solderability: Pb free type is best within 6 months after delivery
- * Humidity sensitive , IPC/JEDEC J-STD-020 MSL if over Level 1, recommend bake 30mins@150 degree before PCBA
- * Caution for human life relative applications : PLS contact & consult with GOTREND team in design stage.

Test Condition :

- * Equipment HP4284A , HP42841A - L , Q , DCR , IDC
HP8753D Network analyzer - SRF
- * Standard Atmosphere Conditions:
Ambient Temperature 20 ± 15 °C
Humidity RH 65 ± 20%
- * If there may be any doubt on the test result ,
Measurement shall be made within the following limits:
Ambient Temperature 25 ± 5 °C
Humidity RH 75 ± 10%

Recommend IR Reflow Curve : GTX-IR-FILE001

Lead Free Solder : A = 217 deg.C , B = 245+/-5 deg.C
Time : C = 40 ~ 60 Sec.



Notice : Iron Soldering , Solder < 30 Watt ,
Direct touch the terminal x 3 Sec. Max. @ 350 deg.C

Product Series :	GTV	Brand :	GOTREND
File Version :	GTV-SERIES-V2R2	Editor :	Jerry Chen
Established Date :	2011.09.21	Description :	SMD Power Inductor
Latest Edit Date :	2023.11.10	Product Type :	☒ Standard ☐ Customize


SMD Power Inductor - GTV Series Type

Image	Part Name	L (mm) Max.	W (mm) Max.	H (mm) Max.	Inductance Range (nH)			DCR (m Ohm)		Isat (A) Max.		Irms (A) Max.	Page
					1	100	1000						
	GTV746632PR1	7.35	6.6	3.18	80 150			1.35 +/- 10%		@25°C 16~50	@125°C 13~27	28	5-6
	GTV707050PR1	7.0	7.0	4.95	72 226			0.25 +/- 8%		@25°C 20~65	@125°C 16~50	43.0	7-8
	GTV707050PR2	7.0	7.0	4.95	72 226			0.32 +/- 7%		@25°C 20~65	@125°C 16~50	38.0	9-10
	GTV707050PR3	7.0	7.0	4.95	Change:	72 226		0.46 +/- 6%		@25°C 20~65	@125°C 16~50	32.0	11-12
	GTV808050PR1	7.62	7.49	4.96	32 200			0.25 +/- 8%		@25°C 20~110	@125°C 16~95	43.0	13-14
	GTV966610PHL	9.6	6.6	10.1	70 220			0.12		46.0 ~ 145.0		84.0	15
	GTV986480PR1	9.8	6.4	8	100 300			0.29 +/- 5%		32.5 ~ 94.0		51.0	16-17
	GTV107049PR1	10.4	7.0	4.95	80 220			0.39 +/- 7.5%		33.0 ~ 90.0		53.0	18-19
	GTV107049PR2	10.4	7.0	4.95	80 220			0.47 +/- 6.5%		33.0 ~ 90.0		50.0	20-21
	GTV107049PR3	10.4	7.0	4.95	80 220			0.55 +/- 5.4%		33.0 ~ 90.0		50.0	22-23
	GTV107049PR4	10.4	7.0	4.95	80 220			0.31 +/- 7%		33.0 ~ 90.0		50.0	24-25
	GTV108070PR1	10.6	8.0	7.0	120 470			0.29 +/- 5.0%		23.5 ~ 94.0		61.0	26-27
	GTV108085PR1	10.4	8.2	8.2	100 300			0.12 Typ.	0.13 Max.	36.0 ~ 109.0		70.0	28
	GTV108080PR1	10.4	8.0	8.0	120 220			0.18 +/- 5%		@25°C 51~95	@125°C 47~77	68.0	29-30
	GTV117070PR1	11.4	7.2	7.2	120 510			0.29 +/- 5%		@25°C 18~90	@125°C 14.5~72	55.0	31-32
	GTV117070PR2	11.4	7.2	7.5	120 510			0.47 +/- 6%		@25°C 18~90	@125°C 14.5~72	42.0	33-34
	GTV128080PR1	12.2	8.1	8.0	150 250			0.29 +/- 5.0%		55.0 ~ 85.0		50.0	35-36

Product Series :	GTV	Brand :	GOTREND
File Version :	GTV-SERIES-V2R2	Editor :	Jerry Chen
Established Date :	2011.09.21	Description :	SMD Power Inductor
Latest Edit Date :	2023.11.10	Product Type :	☒ Standard ☐ Customize

GTV746632PR1-SERIES

Dimension [mm] :



A (Max.)	B (Max.)	C (Max.)	D (+/-0.2)	E (+/-0.2)	F (Ref.)	G (Ref.)	H (Ref.)
7.35	6.60	3.18	2.80	1.65	7.65	3.35	3.25

Electrical Characteristics :

Part No.	Inductance (nH)	Tolerance	Test Freq. (Hz)	DCR (m Ohm)	Isat (A)		Irms (A) Max.
					@25℃	@125℃	
GTV746632PR1-R08K	80	+/-10%	100K / 0.1V	1.35 +/- 10%	32.0	27.0	28.0
GTV746632PR1-R10K	100	+/-10%	100K / 0.1V	1.35 +/- 10%	27.0	23.0	28.0
GTV746632PR1-R12K	120	+/-10%	100K / 0.1V	1.35 +/- 10%	22.0	19.0	28.0
GTV746632PR1-R15K	150	+/-10%	100K / 0.1V	1.35 +/- 10%	16.0	13.0	28.0






* **Test Condition** : @100KHz , 0.1Vrms , 25℃ Ambient

* **Isat** : Saturated Current measured at the point of L drop approximately 20%

* **Irms** : Rated Current Loading when temperature rise approximately 40℃

* **The part temperature (ambient + temp rise)** : Should not exceed 125℃ under worst case operating conditions. Circuit design, component, PCB trace size and thickness, airflow and other cooling provisions all affect the part temperature. Part temperature should be verified in the end application.


Product Series :	GTV	Brand :	GOTREND
File Version :	GTV-SERIES-V2R2	Editor :	Jerry Chen
Established Date :	2011.09.21	Description :	SMD Power Inductor
Latest Edit Date :	2023.11.10	Product Type :	☒ Standard ☐ Customize



Product Series :	GTV	Brand :	GOTREND
File Version :	GTV-SERIES-V2R2	Editor :	Jerry Chen
Established Date :	2011.09.21	Description :	SMD Power Inductor
Latest Edit Date :	2023.11.10	Product Type :	☒ Standard ☐ Customize

GTV707050PR1-SERIES

Dimension [mm] :



A (Max.)	B (Max.)	C (Max.)	D (+/-0.2)	E (+/-0.2)	F (Ref.)	G (Ref.)	H (Ref.)
7.00	7.00	4.95	2.45	1.52	7.4	3.35	3.10

Electrical Characteristics :

Part No.	Inductance (nH)	Tolerance	Test Freq. (Hz)	DCR (m Ohm)	Isat (A)		Irms (A) Max.
					@25℃	@125℃	
GTV707050PR1-R07K	72	+/-10%	100K / 0.1V	0.25 +/- 8%	65.0	50.0	43.0
GTV707050PR1-R10K	105	+/-10%	100K / 0.1V	0.25 +/- 8%	44.0	34.0	43.0
GTV707050PR1-R12K	120	+/-10%	100K / 0.1V	0.25 +/- 8%	37.0	30.0	43.0
GTV707050PR1-R15K	150	+/-10%	100K / 0.1V	0.25 +/- 8%	30.0	24.0	43.0
GTV707050PR1-R18K	180	+/-10%	100K / 0.1V	0.25 +/- 8%	25.0	20.0	43.0
GTV707050PR1-R22K	226	+/-10%	100K / 0.1V	0.25 +/- 8%	20.0	16.0	43.0








* **Test Condition :** @100KHz , 0.1Vrms , 25℃ Ambient

* **Isat :** Saturated Current measured at the point of L drop approximately 20%

* **Irms :** Rated Current Loading when temperature rise approximately 40℃

* **The part temperature (ambient + temp rise) :** Should not exceed 125℃ under worst case operating conditions. Circuit design, component, PCB trace size and thickness, airflow and other cooling provisions all affect the part temperature. Part temperature should be verified in the end application.


Product Series : GTV	Brand : GOTREND
File Version : GTV-SERIES-V2R2	Editor : Jerry Chen
Established Date : 2011.09.21	Description : SMD Power Inductor
Latest Edit Date : 2023.11.10	Product Type : ☒ Standard ☐ Customize



Product Series :	GTV	Brand :	GOTREND
File Version :	GTV-SERIES-V2R2	Editor :	Jerry Chen
Established Date :	2011.09.21	Description :	SMD Power Inductor
Latest Edit Date :	2023.11.10	Product Type :	☒ Standard ☐ Customize

GTV707050PR2-SERIES

Dimension [mm] :










Electrical Characteristics :

Part No.	Inductance (nH)	Tolerance	Test Freq. (Hz)	DCR (m Ohm)	Isat (A)		Irms (A) Max.
					@25℃	@125℃	
GTV707050PR2-R07K	72	+/-10%	100K / 0.1V	0.32 +/- 7%	65.0	50.0	38.0
GTV707050PR2-R10K	105	+/-10%	100K / 0.1V	0.32 +/- 7%	44.0	34.0	38.0
GTV707050PR2-R12K	120	+/-10%	100K / 0.1V	0.32 +/- 7%	37.0	30.0	38.0
GTV707050PR2-R15K	150	+/-10%	100K / 0.1V	0.32 +/- 7%	30.0	24.0	38.0
GTV707050PR2-R18K	180	+/-10%	100K / 0.1V	0.32 +/- 7%	25.0	20.0	38.0
GTV707050PR2-R22K	226	+/-10%	100K / 0.1V	0.32 +/- 7%	20.0	16.0	38.0

- * **Test Condition** : @100KHz , 0.1Vrms , 25℃ Ambient
- * **Isat** : Saturated Current measured at the point of L drop approximately 20%
- * **Irms** : Rated Current Loading when temperature rise approximately 40℃
- * **The part temperature (ambient + temp rise)** : Should not exceed 125℃ under worst case operating conditions. Circuit design, component, PCB trace size and thickness,airflow and other cooling provisions all affect the part temperature. Part temperature should be verified in the end application.


Product Series : GTV	Brand : GOTREND
File Version : GTV-SERIES-V2R2	Editor : Jerry Chen
Established Date : 2011.09.21	Description : SMD Power Inductor
Latest Edit Date : 2023.11.10	Product Type : ☒ Standard ☐ Customize



Product Series :	GTV	Brand :	GOTREND
File Version :	GTV-SERIES-V2R2	Editor :	Jerry Chen
Established Date :	2011.09.21	Description :	SMD Power Inductor
Latest Edit Date :	2023.11.10	Product Type :	☒ Standard ☐ Customize

GTV707050PR3-SERIES

Dimension [mm] :










Electrical Characteristics :

Part No.	Inductance (nH)	Tolerance	Test Freq. (Hz)	DCR (m Ohm)	Isat (A)		Irms (A) Max.
					@25℃	@125℃	
GTV707050PR3-R07K	72	+/-10%	100K / 0.1V	0.46 +/- 6%	65.0	50.0	32.0
GTV707050PR3-R10K	105	+/-10%	100K / 0.1V	0.46 +/- 6%	44.0	34.0	32.0
GTV707050PR3-R12K	120	+/-10%	100K / 0.1V	0.46 +/- 6%	37.0	30.0	32.0
GTV707050PR3-R15K	150	+/-10%	100K / 0.1V	0.46 +/- 6%	30.0	24.0	32.0
GTV707050PR3-R18K	180	+/-10%	100K / 0.1V	0.46 +/- 6%	25.0	20.0	32.0
GTV707050PR3-R22K	226	+/-10%	100K / 0.1V	0.46 +/- 6%	20.0	16.0	32.0

- * **Test Condition** : @100KHz , 0.1Vrms , 25℃ Ambient
- * **Isat** : Saturated Current measured at the point of L drop approximately 20%
- * **Irms** : Rated Current Loading when temperature rise approximately 40℃
- * **The part temperature (ambient + temp rise)** : Should not exceed 125℃ under worst case operating conditions. Circuit design, component, PCB trace size and thickness,airflow and other cooling provisions all affect the part temperature. Part temperature should be verified in the end application.


Product Series : GTV	Brand : GOTREND
File Version : GTV-SERIES-V2R2	Editor : Jerry Chen
Established Date : 2011.09.21	Description : SMD Power Inductor
Latest Edit Date : 2023.11.10	Product Type : ☒ Standard ☐ Customize



Product Series :	GTV	Brand :	GOTREND
File Version :	GTV-SERIES-V2R2	Editor :	Jerry Chen
Established Date :	2011.09.21	Description :	SMD Power Inductor
Latest Edit Date :	2023.11.10	Product Type :	☒ Standard ☐ Customize

GTV808050PR1-SERIES

Dimension [mm] :









Electrical Characteristics :

Part No.	Inductance (nH)	Tolerance	Test Freq. (Hz)	DCR (m Ohm)	Isat (A)		Irms (A) Max.
					@25℃	@125℃	
GTV808050PR1-R03M	32	+/-20%	100K / 0.1V	0.25 +/- 8%	110.0	95.0	43.0
GTV808050PR1-R06L	58	+/-15%	100K / 0.1V	0.25 +/- 8%	83.0	61.0	43.0
GTV808050PR1-R07K	72	+/-10%	100K / 0.1V	0.25 +/- 8%	67.0	49.0	43.0
GTV808050PR1-R10K	100	+/-10%	100K / 0.1V	0.25 +/- 8%	50.0	35.0	43.0
GTV808050PR1-R20K	200	+/-10%	100K / 0.1V	0.25 +/- 8%	20.0	16.0	43.0

- * **Test Condition** : @100KHz , 0.1Vrms , 25℃ Ambient
- * **Isat** : Saturated Current measured at the point of L drop approximately 20%
- * **Irms** : Rated Current Loading when temperature rise approximately 40℃
- * **The part temperature (ambient + temp rise)** : Should not exceed 125℃ under worst case operating conditions. Circuit design, component, PCB trace size and thickness,airflow and other cooling provisions all affect the part temperature. Part temperature should be verified in the end application.


Product Series : GTV	Brand : GOTREND
File Version : GTV-SERIES-V2R2	Editor : Jerry Chen
Established Date : 2011.09.21	Description : SMD Power Inductor
Latest Edit Date : 2023.11.10	Product Type : ☒ Standard ☐ Customize



Product Series :	GTV	Brand :	GOTREND
File Version :	GTV-SERIES-V2R2	Editor :	Jerry Chen
Established Date :	2011.09.21	Description :	SMD Power Inductor
Latest Edit Date :	2023.11.10	Product Type :	☒ Standard ☐ Customize

GTV966610PHL-SERIES

Dimension [mm] :



A (Max.)	B (Max.)	C (Max.)	D (+/-0.2)	E (+/-0.2)	F (Ref.)	G (Ref.)	H (Ref.)
9.60	6.60	10.10	3.20	2.70	10.0	3.40	3.60

Electrical Characteristics :


Part No.	Inductance (nH)	Tolerance	DCR (m Ohm) Max.	Isat (A) Typ.	Irms (A) Typ.
GTV966610PHL-R07K	70	+/-10%	0.12	145.0	84.0
GTV966610PHL-R10K	100	+/-10%	0.12	108.0	84.0
GTV966610PHL-R12K	120	+/-10%	0.12	85.0	84.0
GTV966610PHL-R15K	150	+/-10%	0.12	67.0	84.0
GTV966610PHL-R22K	220	+/-10%	0.12	46.0	84.0

- * **Test Condition** : @100KHz , 0.1Vrms , 25°C Ambient
- * **Isat** : Saturated Current measured at the point of L drop approximately 20%
- * **Irms** : Rated Current Loading when temperature rise approximately 40°C
- * **The part temperature (ambient + temp rise)** : Should not exceed 125°C under worst case operating conditions. Circuit design, component, PCB trace size and thickness, airflow and other cooling provisions all affect the part temperature. Part temperature should be verified in the end application.

Product Series :	GTV	Brand :	GOTREND
File Version :	GTV-SERIES-V2R2	Editor :	Jerry Chen
Established Date :	2011.09.21	Description :	SMD Power Inductor
Latest Edit Date :	2023.11.10	Product Type :	☒ Standard ☐ Customize

GTV986480PR1-SERIES

Dimension [mm] :










Electrical Characteristics :

Part No.	Inductance (nH)	Tolerance	Test Freq. (Hz)	DCR (m Ohm)	Isat (A) Max.	Irms (A) Max.
GTV986480PR1-R10K	100	+/-10%	100K / 0.1V	0.29 +/- 5%	94.0	51.0
GTV986480PR1-R12K	120	+/-10%	100K / 0.1V	0.29 +/- 5%	79.0	51.0
GTV986480PR1-R15K	150	+/-10%	100K / 0.1V	0.29 +/- 5%	65.0	51.0
GTV986480PR1-R22K	220	+/-10%	100K / 0.1V	0.29 +/- 5%	44.0	51.0
GTV986480PR1-R28K	280	+/-10%	100K / 0.1V	0.29 +/- 5%	34.0	51.0
GTV986480PR1-R30K	300	+/-10%	100K / 0.1V	0.29 +/- 5%	32.5	51.0

- * **Test Condition** : @100KHz , 0.1Vrms , 25°C Ambient
- * **Isat** : Saturated Current measured at the point of L drop approximately 20%
- * **Irms** : Rated Current Loading when temperature rise approximately 40°C
- * **The part temperature (ambient + temp rise)** : Should not exceed 125°C under worst case operating conditions. Circuit design, component, PCB trace size and thickness, airflow and other cooling provisions all affect the part temperature. Part temperature should be verified in the end application.


Product Series :	GTV	Brand :	GOTREND
File Version :	GTV-SERIES-V2R2	Editor :	Jerry Chen
Established Date :	2011.09.21	Description :	SMD Power Inductor
Latest Edit Date :	2023.11.10	Product Type :	☒ Standard ☐ Customize



Product Series :	GTV	Brand :	GOTREND
File Version :	GTV-SERIES-V2R2	Editor :	Jerry Chen
Established Date :	2011.09.21	Description :	SMD Power Inductor
Latest Edit Date :	2023.11.10	Product Type :	☒ Standard ☐ Customize

GTV107049PR1-SERIES

Dimension [mm] :









Electrical Characteristics :

Part No.	Inductance (nH)	Tolerance	Test Freq. (Hz)	DCR (m Ohm)	Isat (A) Max.	Irms (A) Max.
GTV107049PR1-R08K	80	+/-10%	100K / 0.1V	0.39 +/- 7.5%	90.0	53.0
GTV107049PR1-R10K	100	+/-10%	100K / 0.1V	0.39 +/- 7.5%	73.0	53.0
GTV107049PR1-R12K	120	+/-10%	100K / 0.1V	0.39 +/- 7.5%	60.0	53.0
GTV107049PR1-R15K	150	+/-10%	100K / 0.1V	0.39 +/- 7.5%	47.0	53.0
GTV107049PR1-R22K	220	+/-10%	100K / 0.1V	0.39 +/- 7.5%	33.0	53.0

- * **Test Condition** : @100KHz , 0.1Vrms , 25°C Ambient
- * **Isat** : Saturated Current measured at the point of L drop approximately 20%
- * **Irms** : Rated Current Loading when temperature rise approximately 40°C
- * **The part temperature (ambient + temp rise)** : Should not exceed 125°C under worst case operating conditions. Circuit design, component, PCB trace size and thickness, airflow and other cooling provisions all affect the part temperature. Part temperature should be verified in the end application.


Product Series : GTV	Brand : GOTREND
File Version : GTV-SERIES-V2R2	Editor : Jerry Chen
Established Date : 2011.09.21	Description : SMD Power Inductor
Latest Edit Date : 2023.11.10	Product Type : ☒ Standard ☐ Customize



Product Series :	GTV	Brand :	GOTREND
File Version :	GTV-SERIES-V2R2	Editor :	Jerry Chen
Established Date :	2011.09.21	Description :	SMD Power Inductor
Latest Edit Date :	2023.11.10	Product Type :	☒ Standard ☐ Customize

GTV107049PR2-SERIES

Dimension [mm] :









Electrical Characteristics :

Part No.	Inductance (nH)	Tolerance	Test Freq. (Hz)	DCR (m Ohm)	Isat (A) Max.	Irms (A) Max.
GTV107049PR2-R08K	80	+/-10%	100K / 0.1V	0.47 +/- 6.5%	90.0	50.0
GTV107049PR2-R10K	100	+/-10%	100K / 0.1V	0.47 +/- 6.5%	73.0	50.0
GTV107049PR2-R12K	120	+/-10%	100K / 0.1V	0.47 +/- 6.5%	60.0	50.0
GTV107049PR2-R15K	150	+/-10%	100K / 0.1V	0.47 +/- 6.5%	47.0	50.0
GTV107049PR2-R22K	220	+/-10%	100K / 0.1V	0.47 +/- 6.5%	33.0	50.0

- * **Test Condition** : @100KHz , 0.1Vrms , 25°C Ambient
- * **Isat** : Saturated Current measured at the point of L drop approximately 20%
- * **Irms** : Rated Current Loading when temperature rise approximately 40°C
- * **The part temperature (ambient + temp rise)** : Should not exceed 125°C under worst case operating conditions. Circuit design, component, PCB trace size and thickness, airflow and other cooling provisions all affect the part temperature. Part temperature should be verified in the end application.


Product Series : GTV	Brand : GOTREND
File Version : GTV-SERIES-V2R2	Editor : Jerry Chen
Established Date : 2011.09.21	Description : SMD Power Inductor
Latest Edit Date : 2023.11.10	Product Type : ☒ Standard ☐ Customize



Product Series :	GTV	Brand :	GOTREND
File Version :	GTV-SERIES-V2R2	Editor :	Jerry Chen
Established Date :	2011.09.21	Description :	SMD Power Inductor
Latest Edit Date :	2023.11.10	Product Type :	☒ Standard ☐ Customize

GTV107049PR3-SERIES

Dimension [mm] :



A (Max.)	B (Max.)	C (Max.)	D (+/-0.2)	E (+/-0.2)	F (Ref.)	G (Ref.)	H (Ref.)
10.4	7.00	4.95	2.50	1.52	10.35	6.35	3.10

Electrical Characteristics :

Part No.	Inductance (nH)	Tolerance	Test Freq. (Hz)	DCR (m Ohm)	Isat (A) Max.	Irms (A) Max.
GTV107049PR3-R08K	80	+/-10%	100K / 0.1V	0.55 +/- 5.4%	90.0	50.0
GTV107049PR3-R10K	100	+/-10%	100K / 0.1V	0.55 +/- 5.4%	73.0	50.0
GTV107049PR3-R12K	120	+/-10%	100K / 0.1V	0.55 +/- 5.4%	60.0	50.0
GTV107049PR3-R15K	150	+/-10%	100K / 0.1V	0.55 +/- 5.4%	47.0	50.0
GTV107049PR3-R22K	220	+/-10%	100K / 0.1V	0.55 +/- 5.4%	33.0	50.0







* **Test Condition** : @100KHz , 0.1Vrms , 25°C Ambient

* **Isat** : Saturated Current measured at the point of L drop approximately 20%

* **Irms** : Rated Current Loading when temperature rise approximately 40°C

* **The part temperature (ambient + temp rise)** : Should not exceed 125°C under worst case operating conditions. Circuit design, component, PCB trace size and thickness, airflow and other cooling provisions all affect the part temperature. Part temperature should be verified in the end application.


Product Series : GTV	Brand : GOTREND
File Version : GTV-SERIES-V2R2	Editor : Jerry Chen
Established Date : 2011.09.21	Description : SMD Power Inductor
Latest Edit Date : 2023.11.10	Product Type : ☒ Standard ☐ Customize



Product Series :	GTV	Brand :	GOTREND
File Version :	GTV-SERIES-V2R2	Editor :	Jerry Chen
Established Date :	2011.09.21	Description :	SMD Power Inductor
Latest Edit Date :	2023.11.10	Product Type :	☒ Standard ☐ Customize

GTV107049PR4-SERIES

Dimension [mm] :



A (Max.)	B (Max.)	C (Max.)	D (+/-0.2)	E (+/-0.2)	F (Ref.)	G (Ref.)	H (Ref.)
10.4	7.00	4.95	2.50	1.52	10.35	6.35	3.10

Electrical Characteristics :

Part No.	Inductance (nH)	Tolerance	Test Freq. (Hz)	DCR (m Ohm)	Isat (A) Max.	Irms (A) Max.
GTV107049PR4-R08K	80	+/-10%	100K / 0.1V	0.31 +/- 7%	90.0	50.0
GTV107049PR4-R10K	100	+/-10%	100K / 0.1V	0.31 +/- 7%	73.0	50.0
GTV107049PR4-R12K	120	+/-10%	100K / 0.1V	0.31 +/- 7%	60.0	50.0
GTV107049PR4-R15K	150	+/-10%	100K / 0.1V	0.31 +/- 7%	47.0	50.0
GTV107049PR4-R22K	220	+/-10%	100K / 0.1V	0.31 +/- 7%	33.0	50.0







* **Test Condition** : @100KHz , 0.1Vrms , 25°C Ambient

* **Isat** : Saturated Current measured at the point of L drop approximately 20%

* **Irms** : Rated Current Loading when temperature rise approximately 40°C

* **The part temperature (ambient + temp rise)** : Should not exceed 125°C under worst case operating conditions. Circuit design, component, PCB trace size and thickness, airflow and other cooling provisions all affect the part temperature. Part temperature should be verified in the end application.


Product Series : GTV	Brand : GOTREND
File Version : GTV-SERIES-V2R2	Editor : Jerry Chen
Established Date : 2011.09.21	Description : SMD Power Inductor
Latest Edit Date : 2023.11.10	Product Type : ☒ Standard ☐ Customize



Product Series :	GTV	Brand :	GOTREND
File Version :	GTV-SERIES-V2R2	Editor :	Jerry Chen
Established Date :	2011.09.21	Description :	SMD Power Inductor
Latest Edit Date :	2023.11.10	Product Type :	☒ Standard ☐ Customize

GTV108070PR1-SERIES

Dimension [mm] :



Electrical Characteristics :

Part No.	Inductance (nH)	Tolerance	Test Freq. (Hz)	DCR (m Ohm)	Isat (A) Max.	Irms (A) Max.
GTV108070PR1-R12K	120	+/-10%	100K / 0.1V	0.29 +/- 5.0%	94.0	61.0
GTV108070PR1-R15K	150	+/-10%	100K / 0.1V	0.29 +/- 5.0%	75.0	61.0
GTV108070PR1-R18K	180	+/-10%	100K / 0.1V	0.29 +/- 5.0%	60.0	61.0
GTV108070PR1-R22K	220	+/-10%	100K / 0.1V	0.29 +/- 5.0%	50.0	61.0
GTV108070PR1-R27K	270	+/-10%	100K / 0.1V	0.29 +/- 5.0%	41.0	61.0
GTV108070PR1-R30K	300	+/-10%	100K / 0.1V	0.29 +/- 5.0%	35.0	61.0
GTV108070PR1-R33K	330	+/-10%	100K / 0.1V	0.29 +/- 5.0%	33.0	61.0
GTV108070PR1-R39K	390	+/-10%	100K / 0.1V	0.29 +/- 5.0%	28.0	61.0
GTV108070PR1-R47K	470	+/-10%	100K / 0.1V	0.29 +/- 5.0%	23.5	61.0











* **Test Condition** : @100KHz , 0.1Vrms , 25°C Ambient

* **Isat** : Saturated Current measured at the point of L drop approximately 20%

* **Irms** : Rated Current Loading when temperature rise approximately 40°C

* **The part temperature (ambient + temp rise)** : Should not exceed 125°C under worst case operating conditions. Circuit design, component, PCB trace size and thickness, airflow and other cooling provisions all affect the part temperature. Part temperature should be verified in the end application.


Product Series :	GTV	Brand :	GOTREND
File Version :	GTV-SERIES-V2R2	Editor :	Jerry Chen
Established Date :	2011.09.21	Description :	SMD Power Inductor
Latest Edit Date :	2023.11.10	Product Type :	☒ Standard ☐ Customize



Product Series :	GTV	Brand :	GOTREND
File Version :	GTV-SERIES-V2R2	Editor :	Jerry Chen
Established Date :	2011.09.21	Description :	SMD Power Inductor
Latest Edit Date :	2023.11.10	Product Type :	☒ Standard ☐ Customize

GTV108085PR1-SERIES

Dimension [mm] :



A (Max.)	B (Max.)	C (Max.)	D (+/-0.2)	E (+/-0.2)	F (Ref.)	G (Ref.)	H (Ref.)
10.4	8.20	8.20	2.40	3.40	10.8	4.00	3.80

Electrical Characteristics :

Part No.	Inductance (nH)	Inductance 2 (nH) @Isat	Inductance Tolerance	DCR (m Ohm)		Isat (A) Max.	Irms (A) Max.
				Typ.	Max.		
GTV108085PR1-R10K	100.0	72.0 Min.	K	0.12	0.13	109.0	70.0
GTV108085PR1-R12K	120.0	86.0 Min.	K	0.12	0.13	91.0	70.0
GTV108085PR1-R15K	150.0	108.0 Min.	K	0.12	0.13	72.0	70.0
GTV108085PR1-R30K	300.0	216.0 Min.	K	0.12	0.13	36.0	70.0

* **Test Condition** : @100KHz , 0.1Vrms , 25°C Ambient

* Inductance Tolerance : K = +/-10%

* **Isat** : Saturated Current measured at the point of L drop approximately 20%


* **Irms** : Rated Current Loading when temperature rise approximately 40°C

* **The part temperature (ambient + temp rise)** : Should not exceed 125°C under worst case operating conditions. Circuit design, component, PCB trace size and thickness, airflow and other cooling provisions all affect the part temperature. Part temperature should be verified in the end application.

Product Series :	GTV	Brand :	GOTREND
File Version :	GTV-SERIES-V2R2	Editor :	Jerry Chen
Established Date :	2011.09.21	Description :	SMD Power Inductor
Latest Edit Date :	2023.11.10	Product Type :	☒ Standard ☐ Customize

GTV108080PR1-SERIES

Dimension [mm] :



A (Max.)	B (Max.)	C (Max.)	D (+/-0.1)	E (+/-0.2)	F (Ref.)	G (Ref.)	H (Ref.)
10.40	8.00	8.00	2.10	2.54	11.2	4.06	2.50

Electrical Characteristics :

Part No.	Inductance (nH)	Tolerance	Test Freq. (Hz)	DCR (m Ohm)	Isat (A)		Irms (A) Max.
					@25℃	@125℃	
GTV108080PR1-R12K	120	+/-10%	100K / 0.1V	0.18 +/- 5%	95.0	77.0	68.0
GTV108080PR1-R15K	150	+/-10%	100K / 0.1V	0.18 +/- 5%	79.0	66.0	68.0
GTV108080PR1-R18K	180	+/-10%	100K / 0.1V	0.18 +/- 5%	62.0	52.0	68.0
GTV108080PR1-R22K	220	+/-10%	100K / 0.1V	0.18 +/- 5%	51.0	47.0	68.0






* **Test Condition :** @100KHz , 0.1Vrms , 25℃ Ambient

* **Isat :** Saturated Current measured at the point of L drop approximately 20%

* **Irms :** Rated Current Loading when temperature rise approximately 40℃

* **The part temperature (ambient + temp rise) :** Should not exceed 125℃ under worst case operating conditions. Circuit design, component, PCB trace size and thickness, airflow and other cooling provisions all affect the part temperature. Part temperature should be verified in the end application.


Product Series : GTV	Brand : GOTREND
File Version : GTV-SERIES-V2R2	Editor : Jerry Chen
Established Date : 2011.09.21	Description : SMD Power Inductor
Latest Edit Date : 2023.11.10	Product Type : ☒ Standard ☐ Customize



Product Series :	GTV	Brand :	GOTREND
File Version :	GTV-SERIES-V2R2	Editor :	Jerry Chen
Established Date :	2011.09.21	Description :	SMD Power Inductor
Latest Edit Date :	2023.11.10	Product Type :	☒ Standard ☐ Customize

GTV117070PR1-SERIES

Dimension [mm] :










Electrical Characteristics :

Part No.	Inductance (nH)	Tolerance	Test Freq. (Hz)	DCR (m Ohm)	Isat (A)		Irms (A) Max.
					@25℃	@125℃	
GTV117070PR1-R12K	120	+/-10%	100K / 0.1V	0.29 +/- 5%	90.0	72.0	55.0
GTV117070PR1-R15K	150	+/-10%	100K / 0.1V	0.29 +/- 5%	70.0	56.0	55.0
GTV117070PR1-R23K	230	+/-10%	100K / 0.1V	0.29 +/- 5%	45.0	36.0	55.0
GTV117070PR1-R30K	300	+/-10%	100K / 0.1V	0.29 +/- 5%	35.0	28.0	55.0
GTV117070PR1-R40K	400	+/-10%	100K / 0.1V	0.29 +/- 5%	25.0	20.0	55.0
GTV117070PR1-R51K	510	+/-10%	100K / 0.1V	0.29 +/- 5%	18.0	14.5	55.0

- * **Test Condition** : @100KHz , 0.1Vrms , 25℃ Ambient
- * **Isat** : Saturated Current measured at the point of L drop approximately 20%
- * **Irms** : Rated Current Loading when temperature rise approximately 40℃
- * **The part temperature (ambient + temp rise)** : Should not exceed 125℃ under worst case operating conditions. Circuit design, component, PCB trace size and thickness,airflow and other cooling provisions all affect the part temperature. Part temperature should be verified in the end application.


Product Series :	GTV	Brand :	GOTREND
File Version :	GTV-SERIES-V2R2	Editor :	Jerry Chen
Established Date :	2011.09.21	Description :	SMD Power Inductor
Latest Edit Date :	2023.11.10	Product Type :	☒ Standard ☐ Customize



Product Series :	GTV	Brand :	GOTREND
File Version :	GTV-SERIES-V2R2	Editor :	Jerry Chen
Established Date :	2011.09.21	Description :	SMD Power Inductor
Latest Edit Date :	2023.11.10	Product Type :	☒ Standard ☐ Customize

GTV117070PR2-SERIES

Dimension [mm] :



A (Max.)	B (Max.)	C (Max.)	D (+/-0.15)	E (+/-0.2)	F (Ref.)	G (Ref.)	H (Ref.)
11.40	7.20	7.50	1.90	2.50	11.2	5.00	2.10

Electrical Characteristics :

Part No.	Inductance (nH)	Tolerance	Test Freq. (Hz)	DCR (m Ohm)	Isat (A)		Irms (A) Max.
					@25℃	@125℃	
GTV117070PR2-R12K	120	+/-10%	100K / 0.1V	0.47 +/- 6%	90.0	72.0	42.0
GTV117070PR2-R15K	150	+/-10%	100K / 0.1V	0.47 +/- 6%	70.0	56.0	42.0
GTV117070PR2-R23K	230	+/-10%	100K / 0.1V	0.47 +/- 6%	45.0	36.0	42.0
GTV117070PR2-R30K	300	+/-10%	100K / 0.1V	0.47 +/- 6%	35.0	28.0	42.0
GTV117070PR2-R40K	400	+/-10%	100K / 0.1V	0.47 +/- 6%	25.0	20.0	42.0
GTV117070PR2-R51K	510	+/-10%	100K / 0.1V	0.47 +/- 6%	18.0	14.5	42.0








* **Test Condition** : @100KHz , 0.1Vrms , 25℃ Ambient

* **Isat** : Saturated Current measured at the point of L drop approximately 20%

* **Irms** : Rated Current Loading when temperature rise approximately 40℃

* **The part temperature (ambient + temp rise)** : Should not exceed 125℃ under worst case operating conditions. Circuit design, component, PCB trace size and thickness, airflow and other cooling provisions all affect the part temperature. Part temperature should be verified in the end application.


Product Series : GTV	Brand : GOTREND
File Version : GTV-SERIES-V2R2	Editor : Jerry Chen
Established Date : 2011.09.21	Description : SMD Power Inductor
Latest Edit Date : 2023.11.10	Product Type : ☒ Standard ☐ Customize



Product Series :	GTV	Brand :	GOTREND
File Version :	GTV-SERIES-V2R2	Editor :	Jerry Chen
Established Date :	2011.09.21	Description :	SMD Power Inductor
Latest Edit Date :	2023.11.10	Product Type :	☒ Standard ☐ Customize

GTV128080PR1-SERIES

Dimension [mm] :



Electrical Characteristics :

Part No.	Inductance (nH)	Tolerance	Test Freq. (Hz)	DCR (m Ohm)	Isat (A) Max.	Irms (A) Max.
GTV128080PR1-R15K	150	+/-10%	100K / 0.1V	0.29 +/- 5.0%	85.0	50.0
GTV128080PR1-R18K	180	+/-10%	100K / 0.1V	0.29 +/- 5.0%	72.0	50.0
GTV128080PR1-R21K	210	+/-10%	100K / 0.1V	0.29 +/- 5.0%	65.0	50.0
GTV128080PR1-R23K	230	+/-10%	100K / 0.1V	0.29 +/- 5.0%	61.0	50.0
GTV128080PR1-R25K	250	+/-10%	100K / 0.1V	0.29 +/- 5.0%	55.0	50.0







* **Test Condition** : @100KHz , 0.1Vrms , 25°C Ambient

* **Isat** : Saturated Current measured at the point of L drop approximately 20%

* **Irms** : Rated Current Loading when temperature rise approximately 40°C

* **The part temperature (ambient + temp rise)** : Should not exceed 125°C under worst case operating conditions. Circuit design, component, PCB trace size and thickness, airflow and other cooling provisions all affect the part temperature. Part temperature should be verified in the end application.

Product Series :	GTV	Brand :	GOTREND
File Version :	GTV-SERIES-V2R2	Editor :	Jerry Chen
Established Date :	2011.09.21	Description :	SMD Power Inductor
Latest Edit Date :	2023.11.10	Product Type :	☒ Standard ☐ Customize



Product Series :	GTV	Brand :	GOTREND
File Version :	GTV-SERIES-V2R2	Editor :	Jerry Chen
Established Date :	2011.09.21	Description :	SMD Power Inductor
Latest Edit Date :	2023.11.10	Product Type :	☒ Standard ☐ Customize

Care note :

Care note for Use :

(1) Storage Condition :

Temperature 25 to 35°C , Humidity 45 to 60% RH

(2) Use Temperature :

Changed all Marking uses inductance value

- a. Minimum Temperature : -40°C Ambient temperature of this product.
- b. Maximum Temperature : +125°C The value of temperature including ambient and temperature rise of this product.
- c. Reliability test temperature range from -40 ~ +125°C
- d. However, this is not meant as temperature grade guarantee for UL.

(3) Model :

When this product was used in a similar or as new product to the original one, sometimes it might be unable to satisfy the specifications due to difference in condition of usage.

(4) Drop :

If this product suffered mechanical stress such as drop, characteristics may become poor (due to damage on coil / bobbin / ferrite ... etc.)

Never use such stressed product.

Care note for Safety :

(1) Provision to Abnormal Condition :

This product itself does not have any protective function in abnormal condition such as overload, short-circuit and open-circuit conditions, etc.

Therefore, it shall be confirmed from the end product that there is no risk of smoking, fire, dielectric withstand voltage insulation resistance, etc. in abnormal conditions to provide protective devices and /or protection circuit in the end product.

(2) Temperature Rise :

Temperature rise on this product depends on the installation condition on end products.

It shall be confirmed on the actual end product that temperature rise of this product is within the specified temperature class limit.

(3) Dielectric Strength :

Dielectric withstanding test with higher voltage than specific value will damage insulating material and shorten its life.

(4) Water :

This product must not be used in wet condition resulted from water, coffee or any liquid contact because insulation strength becomes very low under such condition.

(5) Potting :




If this product is potted in some compound, coating material of magnet wire might be occasionally damaged. Please ask us if you intend to pot this product.

(6) Detergent :

Please consult our company immediately once under such circumstances because product reliability confirmation etc. is needed when this product come in contact with these chemicals.

Product Series :	GTV	Brand :	GOTREND
File Version :	GTV-SERIES-V2R2	Editor :	Jerry Chen
Established Date :	2011.09.21	Description :	SMD Power Inductor
Latest Edit Date :	2023.11.10	Product Type :	☒ Standard ☐ Customize


Reliability :

SN	Test Item	Test Condition	Specification
1	Dimension	Actual Size ...	Meet Spec
2	Thermal Shock (Temperature Cycle)	Temperature : -40 ~ +125°C kept stabilized for 30 min. each Cycle : 100 Cycles (power off)	Elec. no variation Appearance no deformation
3	Humidity Resistance	Humidity : 90% ~ 95% RH Temperature : 60 ± 2°C, Test Time : 96 ± 2 Hours	Elec. no variation Appearance no deformation
4	High Temperature	Temperature : 125 ± 2°C Testing Time : 96 ± 2 Hours	Elec. no variation Appearance no deformation
5	Low Temperature	Temperature : -40 ± 2°C Time : 96 ± 2 Hours	Elec. no variation Appearance no deformation
6	Temperature and Humidity Cycle	Temperature	Humidity
		25°C	90% ~ 95% RH
		55°C	95% ~ 96% RH
		25°C	90% ~ 95% RH
		Time	
		3.0 Hr	
		5.0 Hr	
		3.0 Hr	
		Cycle : 20 Cycles	
7	Vibration	Frequency : 10Hz ~ 55Hz, Amplitude : 1.5 mm Direction : X, Y, Z, Time : 2 Hours each	Elec. no variation Appearance no deformation
8	Solderability	Go through real SMT IR-Reflow The profile like our suggest profile. Preheat : 160 ± 10°C (90 sec) Peak : 245 ± 5°C Peak Time : 50 Sec. / up 217°C	Elec. no variation Appearance no deformation
9	Soldering Heat Resistance	Preheat : 160 ± 10°C (90 sec) Solder : Sn / Ag / Cu (Pb Free) Solder Temp. : 260 ± 5°C, Time : 3 ± 1 seconds	Elec. no variation Appearance no deformation
10	Iron Solder Heat Resistance	Solder Temp. : 350 ± 5°C Flux : Rosin, Time : 3 ± 1 seconds	Elec. no variation Appearance no deformation
11	Bending Strength	Unit : mm  Force : 1Kg / min.	Elec. no variation Appearance no deformation
12	Flexure Strength	Unit : mm  Solder cream 0.15 mm	Elec. no variation Appearance no deformation
13	Terminal Strength	 Mount on PCB Solder Cream 0.15 mm Push 10N force to X, Y direction	Elec. no variation Appearance no deformation
14	High-Voltage	100 V DC between core & winding	Elec. no variation Appearance no deformation
15	Load life	Temperature : 25 ± 3°C Load : Allowed DC Current, Test Time : 96 ± 2 Hours	Elec. no variation Appearance no deformation

Product Series :	GTV	Brand :	GOTREND
File Version :	GTV-SERIES-V2R2	Editor :	Jerry Chen
Established Date :	2011.09.21	Description :	SMD Power Inductor
Latest Edit Date :	2023.11.10	Product Type :	☒ Standard ☐ Customize


Packaging Information :

Tape Dimension Schematic Diagram (mm):



SIZE/mm	W	P	A0	B0	K0	T	F
746632	16.0	12.0	6.6	7.5	3.3	0.35	7.5
707050	16.0	12.0	7.2	7.2	5.1	0.35	7.5
808050	16.0	12.0	7.7	7.9	5.1	0.35	7.5
966610	24.0	12.0	6.6	10.0	10.3	0.4	11.5
986480	24.0	12.0	6.7	10.3	8.2	0.4	11.5
107049	24.0	12.0	7.4	10.5	5.1	0.4	11.5
108070	24.0	16.0	8.2	10.7	7.6	0.4	11.5
108085	24.0	16.0	8.4	10.5	8.3	0.4	11.5
108080	24.0	16.0	8.2	10.8	8.25	0.4	11.5
117070	24.0	16.0	7.5	11.6	7.6	0.4	11.5
128080	24.0	12.0	8.4	12.5	8.3	0.4	11.5

Reel Dimension Schematic Diagram (mm):




SIZE/mm	Reel Size	A	B	C	D	QTY / Reel
746632	13" x 16 mm	330	100	20.4	16.5	1500 PCS
707050	13" x 16 mm	330	100	20.4	16.5	1000 PCS
808050	13" x 16 mm	330	100	20.4	16.5	1000 PCS
966610	13" x 24 mm	330	100	20.4	24.5	500 PCS
986480	13" x 24 mm	330	100	20.4	24.5	700 PCS
107049	13" x 24 mm	330	100	20.4	24.5	1000 PCS
108070	13" x 24 mm	330	100	20.4	24.5	500 PCS
108085	13" x 24 mm	330	100	20.4	24.5	500 PCS
108080	13" x 24 mm	330	100	20.4	24.5	500 PCS
117070	13" x 24 mm	330	100	20.4	24.5	500 PCS
128080	13" x 24 mm	330	100	20.4	24.5	700 PCS

Product Series :	GTV	Brand :	GOTREND
File Version :	GTV-SERIES-V2R2	Editor :	Jerry Chen
Established Date :	2011.09.21	Description :	SMD Power Inductor
Latest Edit Date :	2023.11.10	Product Type :	☒ Standard ☐ Customize

Packaging Information :


Tearing Off Force :




The force for tearing off cover tape is 10 to 130 grams in the arrow direction under the following conditions (referenced ANSI / EIA - 481 - D - 2008 of 4.11stadnard).

Room Temp. (°C)	Room Humidity (%)	Room Atm. (hPa)	Tearing Speed (mm / min)
5 ~ 35	45 ~ 85	860 ~ 1060	300

Box Package Schematic Diagram:



13" Small Box



13" Large Box

SIZE/mm	Reels size	A	B	C	Large Box size	D	E	F	Reels in Small Box (QTY)	Small Box in Large Box(QTY)
746632	13"	335	335	23	13"	350	350	220	1(1500)	7(10500)
707050	13"	335	335	23	13"	350	350	220	1(1000)	7(7000)
808050	13"	335	335	23	13"	350	350	220	1(1000)	7(7000)
966610	13"	335	335	23	13"	350	350	220	1(500)	5(2500)
986480	13"	335	335	23	13"	350	350	220	1(700)	5(3500)
107049	13"	335	335	40	13"	350	350	220	1(1000)	5(5000)
108070	13"	335	335	40	13"	350	350	220	1(500)	5(2500)
108085	13"	335	335	40	13"	350	350	220	1(500)	5(2500)
108080	13"	335	335	40	13"	350	350	220	1(500)	5(2500)
117070	13"	335	335	40	13"	350	350	220	1(500)	5(2500)
128080	13"	335	335	40	13"	350	350	220	1(700)	5(3500)